



**TP3000120WIPCEE – 3700 619 438 627**

REGLETTE LED ETANCHE IP65 230V



IP65

**ULR**

< 3%



CONS : **24W**



3500 LM

**145lm/W**

EFFICACITÉ LUMINEUSE

**LED**

SOURCE REMPLACABLE

**3 ans**  
years



230V~50Hz



3000K – 4000K



120°

**DIM:**  
1200 x70  
x62mm

**IRC**

>80

**IK**

8



CONNECTEUR RAPIDE



25 000H



CLASS I

**CE**

Conforme à l'arrêté du 27 Décembre 2018 relatif à la prévention , à la réduction des nuisances lumineuses

Cerf/Test report	Directive	Normes
EMC	2014/30/EU	<ul style="list-style-type: none"> <li>EN IEC 55015 : 2019 + A11 : 2020</li> <li>EN IEC 61000-3-2 : 2019</li> <li>EN 61000-3-3 : 2013 + A1 : 2019</li> <li>EN 61547 : 2009</li> </ul>
LVD	2014/35/EU	<ul style="list-style-type: none"> <li>EN IEC 60598-1 : 2021</li> <li>EN IEC 60598-2-3: 2003+A1 :2011</li> <li>EN 62493 : 2015</li> <li>EN 62471 : 2008</li> </ul>
Rohs	2011/65/EU	

Facteur de puissance > 0.9  
Durée de vie : 25 000H  
3000K – 4000K  
Source lumineuse remplaçable  
Alu + PC

Pour un ULR conforme à l'arrêté il convient de ne pas dépasser une inclinaison de 25° par rapport à l'horizontale

CEE Fiches : RES-EC-104 (A14-1) prorogée depuis 2021 Dec.  
Rénovation d'éclairage extérieur